




FOR THE CORRECT WORKING OF THE FSA: IF YOU HAVE A RHD (RIGHT HAND DRIVE) CAR, YOU HAVE TO READ "LEFT", AS "RIGHT".

So, for example, you have to connect your right channel from the source to the "LEFT" channel of your GLADEN ONE amplifier. In the output, connect your right side speaker to the "LEFT" section.

<p>Verbindungsleitung</p> <p>NEGATIVE POWER CONNECTION</p> <p>Securely connect the clamp to a metallic part of the frame or chassis of the vehicle. Strip the paint and debris, and use the shortest possible cable with the proper terminal.</p>	<p>FRONT LEFT and FRONT RIGHT terminals to reproduce the audio input in the RCA</p> <p>FRONT LEFT and FRONT RIGHT respectively.</p> <p>Connect the speakers to the BRIDGE terminals to reproduce a mixed signal from the RCA FRONT LEFT and FRONT RIGHT terminals to reproduce the audio input in the RCA</p>	<p>REAR LEFT and REAR RIGHT respectively.</p> <p>Connect the speakers to the BRIDGE terminals to reproduce a mixed signal from the RCA REAR LEFT and REAR RIGHT terminals to reproduce the audio input in the RCA</p>
<p>POSITIVE POWER CONNECTION</p> <p>Securely Connect the clamp to the positive lead of the battery. Use the shortest possible cable with the proper terminal. We recommend using an external fuse as close as possible to the battery.</p>	<p>Before replacing the fuse, power off the audio source and then disconnect the battery.</p> <p>Remove the blown fuse and replace it with the same model and rating (same maximum amp)</p>	<p>FUSE</p> <p>Entfernen Sie die defekte Sicherung und ersetzen Sie diese mit einer Sicherung der gleichen Größe</p> <p>Possible causes:</p> <ul style="list-style-type: none"> 1) The power supply is inadequate 2) The fuse has blown 3) The power voltage is below 7 VDC 4) The amplifier is malfunctioning <p>Remedy:</p> <ul style="list-style-type: none"> 1) Verify and restore the connections and the contacts of the power circuit 2) Replace the fuse 3) Recharge or replace the vehicle's battery 4) Contact an authorized reseller to initiate the procedure for Technical Assistance
<p>RED: the amplifier is powered on but is not functioning. Cycle the power to verify proper operation.</p>	<p>RED: the amplifier is powered on but is not functioning. Cycle the power to verify proper operation.</p>	<p>RED: the amplifier is powered on but is not functioning. Cycle the power to verify proper operation.</p>



FOR THE CORRECT WORKING OF THE FSA: IF YOU HAVE A RHD (RIGHT HAND DRIVE) CAR, YOU HAVE TO READ “LEFT” AS “RIGHT” OR THE CORRECT WORKING OF THE FSA: IF YOU HAVE A RHD (RIGHT HAND DRIVE) CAR, YOU HAVE TO READ “LEFT” AS “RIGHT”

In the output, connect your right side speaker to the “LEFT” channel of your GLADEN ONE amplifier. In the output, connect your right side speaker to the “LEFT” channel from the source to the “LEFT” channel of your GLADEN ONE amplifier.