

COAXIAL

My 6X

- 1 Surround in gomma.
- 2 Gasket in ABS per iniezione.
- 3 Cono in FIBREGLASS.
- 4 Trecciole argentate.
- 5 Tweeter al neodimio.
- 6 Terminali 4,8x7,2 mm.
- 7 Cestello a norme DIN in lamiera con trattamento texture anti-corrosivo.

Frequency range	78 - 20000	Hz
Equivalent volume, Vas	9.968	L
Compliance, Cms	0.0035	mm/N
Mechanical resistance, Rms	3.6	Ns/m
Effective diaphragm/cone area, Sd	141	cm ²
Voice coil diameter	25.9	mm
Voice coil height	7	mm
Air gap height	4	mm
Linear excursion, Xmax	± 1.5	mm
Max mechanical excursion	± 8	mm
Nominal impedance	4	ohm
Voice coil resistance	4.14	ohm
Voice coil inductance	0.204	mH
Free air resonance, Fs	77.44	Hz
Sensitivity, Spl (2.83V/1m)	90.7	dB
Force factor, Bxl	3.144	Tm
Moving mass, Md	11.963	g
Qms	2.506	
Qes	2.438	
Qts	1.236	
Nominal power	60	W
Short term max power	240	W
Long term max power	120	W

