

COMP diECi

DT 24.3

80 W



Compact **SIZE**


Technical Specifications

Component	-	Tweeter
Size	mm (in.)	24 (0.9)
Power handling	W peak	80 W @ 3,5 kHz 6 dB Oct
	W continuous	-
Impedance	Ω	4
Frequency response	Hz	3k - 23k
Sensitivity	dB SPL	94
Magnet size D-d-h	mm (in.)	-
Voice coil Ø	mm (in.)	-
Magnet	-	Neodymium
Dome	-	PEI
Weight of one component	kg (lb.)	0,03 (0.07)
Crossover	-	Hi Pass
Crossover cut off	-	3,5 kHz @ 6 dB Oct


1. Tweeter con cupola da 24 mm in PEI.
2. Lente acustica anulare ad alta efficienza
3. Magnete al neodimio ad alta energia.
4. Supporti in dotazione per il montaggio sia in superficie che a incasso.

Electro-Acoustic Parameters

D	mm	24
Xmax	mm	-
Re	Ω	3,3
Fs	Hz	2800
Le	mH @ 1 kHz	0,3
Le	mH @ 10 kHz	0,04
Vas	l	-
Mms	g	-
Cms	mm/N	-
BL	T-m	-
Qts	-	-
Qes	-	-
Qms	-	-
Spl	dB	94



G	44 mm (1.7 in.)
H	26 mm (1.0 in.)
I	20 mm (0.8 in.)



A	34 mm (1.3 in.)
B	-
C	20 mm (0.8 in.)
D	13 mm (0.5 in.)

MOUNTING ACCESSORIES

